HAS A WIDE VARIETY OF **ROOF COATINGS**?

HELPS ME ADD **INSULATION** TO MY HOME?

CARRIES **A LARGE INVENTORY** OF MOBILE HOME PARTS?

OFFERS A WIDE SELECTION OF **SEALANTS** AND **CAULKS**?

THE ANSWER IS



Roof Coatings

ANVIL PREMIUM FIBERED FLASTOMERIC WHITE ROOF COATING

May be applied over new galvanized surfaces. Dries in 30-60 minutes. Second coat can be applied in 1-2 hours. Will not chalk, peel or drip. Coverage: approx. 150 sq. ft. per gallon for two coat coverage.



0110215 5 GALLONS 0110217 1 GALLON: 4/CTN.

MOBILE HOME WHITE **ELASTOMERIC**

Water-based, specifically formulated with 100% acrylic resin for mobile homes. 5-year guarantee. Remains flexible from -10° to 160° F. No mixing, soap and water cleanup when wet.

chemicals or solvents. VOC=less than 60

Class A fire rating. No hazardous



ALUMA-KOTE FIBERED ALUMINUM

ANVIL ELASTOMERIC WHITE ROOF COATING

Superior performance and brilliant white

good looks, superior to the usual home center

products on the market, for when you need

a competitively priced all-round elastomeric

An economy fibered, reflective aluminum roof coating that protects and renews worn roof surfaces. Dries to an aluminum/

silver color. Can be used for asphalt shingles or dead flat roofs with slopes less than 54 degrees (or 1/8" per ft.). Approximate Coverage Area (Sq. Feet) 250.*



0110650 5 GALLONS

alternative.

0110225 5 GALLON

0110342 4.75 GALLONS

grams/liter. UL approved

WHITE ELASTOMERIC

Ultra-high reflectivity for metal. concrete. bonded tar and gravel, foam, brick, wood, flat and barrel cement tile roofs.

100% acrylic elastomeric resin to keep interiors cooler with energy savings of up to 35%. Covers approx. 75-100 sq. ft. per gallon.



0110331 0.9 GALLON; 4/CTN. 0110332 4.75 GALLONS

BLUE LABEL ALUMINUM **ROOF COATING**

Ultra-high Performance for metal, asphalt, modified bitumen & rolled roofing.

KOOL SEAL 7YR

Coat with Kool Seal Elastomeric Roof Coating

cooler and reduce energy costs-up to 35%!

to protect buildings from the elements for

years. Highly reflective to keep interiors

ELASTOMERIC

Protects against moisture with a unique asphalt and aluminum formula. Reduces heat build-up to keep interiors cooler with energy savings of up to 30%. Covers approx. 80-100 sq. ft., 5-year warranty.



ALUMINUM ECONOMY ROOF COATING

For metal, asphalt, modified bitumen and rolled roofing

Asphalt based aluminum protects against moisture and damaging UV rays for energy savings of up to 20%. Covers approx. 50 sq. ft. per gallon.



0110108 0.9 GALLON; 4/CTN. 0110110 4.75 GALLONS

KOOL-FLEXX BLUE REINFORCING GRID

Strong, flexible grid covers cracks 1/4" or more, seams and stress areas on existing roofing materials. Will not rot or corrode. Use with roof coating.



0110410 4" X 40'

0110347 4.75 GALLONS

0110105 4.75 GALLONS



Roof Coatings

KOOL-PATCH WHITE PATCHING CEMENT

Kool Seal White Acrylic Patching Cement patches tough leaks and won't run or sag! After application it retains its flexibility to resist cracking, peeling, and blistering.



0110341 0.9 GALLON; 4/CTN.

BLACK JACK ROOF CEMENT



Asphalt sealer-filler patches cracks in roofing, firewalls, chimneys, gutters, flashing, etc. particularly for emergency repairs of wet surfaces. Apply with standard caulking gun. Cleanup with paint thinner or mineral spirits. Flexible, Cannot be painted.

0110425 10 OZ.; 12/CTN.

LEAK STOPPER

- Lasts 2 3x longer than standard patches
- Specially designed for problem leaks
- Stops roof leaks instantly
- Permanent Repair •
- Use in wet or dry conditions
- Rubberized to prevent cracking

Made with Penetrex[™], a unique penetrating oil that forms a complete seal.

Apply with a trowel or putty knife. Covers approx. 12 sq. ft. per gallon when applied 1/8" thick.

0110420 10.1 OZ. TUBE

ANVIL PATCHER/ SEALER

Textured, ideal for sealing seams on roofs

and awning rails. Adheres to any surface,

such as galvanized roofing, without preparation.

0110220 GALLON

STORM PATCH WET/DRY **ROOF CEMENT**

All-weather, elastomeric, asphalt wet patch/roof cement. It displaces water from a wet surface and forms a tight seal. Can be used in hot or cold weather applications.



0110345 0.9 GALLON

STORM PATCH CLEAR **ROOF CEMENT**



All-weather, clear, elastic sealant with excellent adhesion. Ideal for sealing leaks around vents, gutters, skylights and other roof materials when an invisible patch is desired. Wet/cold application.

0110346 10 FL OZ

FIRESTOP SEALANT



Water-based, is intended to use in UL classified throughpenetration firestop systems. Pale red color.

0119026 10.1 OZ.; 12/CTN




A proprietary non-flammable, intumescing (expands up to 2000%) interior coating that provides oxygen starvation to fire. It is a non-toxic, water based, drain safe, no fuming GREEN product. It is a waterbased one part coating system that comes white but can be tinted different colors.



0340155 10 0Z.; 12/CTN.

ROOFING BRUSH & HANDLE





93

PEEL & SEAL SELF-STICK ROLL ROOFING

Peel off the release paper, press the material into place. It's that simple.

The perfect solution for low slope and dozens of other roofing problems, Peel & Seal installs using only a utility knife. You can forget big crews, hot kettles, torches, adhesives and fasteners. No coating is necessary. Adheres to most surfaces. It won't crack or dry out.

Replaces old style rolled roofing products. It seals around most punctures. Perfect answer to roofing, waterproofing, patching, and repair.



Rolls are 33.5 feet long.



0110350 ALUMINUM 6"; 6/CTN. 0110351 WHITE 6"; 6 CTN. 0110352 ALUMINUM 36"; 1/CTN. 0110353 WHITE 36"; 1/CTN. 0110354 ALUMINUM 18"; 1/CTN. 0110355 ALUMINUM 12"; 1/CTN.

DYCO C-10[®] HYPALON FLOW SEAL CAULK

Self-leveling, paintable, fast drying, weather resistant, will not surface harden or crack. Resists mold and mildew, fungus and bacteria. When cured, resists water, oil, grease, gasoline and many other chemicals. Dries in 30 to 60 minutes. Recommended for horizontal surfaces such as roofs on RVs, mobile homes, metal buildings, roofovers, vents, seams, inside gutters, etc. Easy cleanup with xylene solvent.



GE MAX 3500

Combines the performance of silicone with the ease of use of latex caulk. Lifetime durability. Adheres to aluminum, glass, PVC, steel, concrete, brick, polystyrene foam and wood. Paintable. Good joint movement capability. Mildew resistant. Water clean up.

0119008 CLEAR 10 OZ 0119009 WHITE 10 OZ



0110450 GRAY 11 OZ. TUBE. 0110451 WHITE 11 OZ. TUBE.

GE ADVANTAGE SILICONE CAULK

Permanently weatherproof and watertight sealant. Will not crack, crumble, dry out or peel. Remains permanently flexible. Adheres to most building materials; glass, masonry, metals and woods.



0119018 CLEAR 10.1 OZ

GE MAX 5000

A high performance urethane modified latex acrylic. Lifetime durability. Excellent adhesion to wood, glass, metal and aluminum. Great flexibility. Paintable and cleans up with water. Great for log homes. Use as a radon gas barrier. Mildew proof. Tack free in 30 minutes. Full cure in 3 days.

0119016 WHITE 10 OZ 0119017 CLEAR 10 OZ



CAULKING GUN

Use with cartridges. Spring grip maintains steady pressure and even bead.

0112401



CAULK FINISHER

Scoops away excess caulk for a professionally finished joint. Works with all types of caulks and silicone sealers. Can be trimmed to desired bead for a variety of jobs.

0112402

DAP ALEX PLUS CAULK WITH SILICONE

ALEX PLUS

Superior quality, multi-purpose acrylic latex caulk plus silicone. Highly flexible and durable. Excellent adhesion. Cured caulk is mildew resistant. Interior/exterior use. Paintable. Water clean-up. 35 year durability guarantee. Exceeds ASTM specification C 834. Sealing around wood, vinyl, and aluminum siding & trim, caulking around windows and doors 10.1 fl oz.

0119010 CLEAR 0119011 WHITE

SKYLIGHT SEALANT/CAULK

A non-skinning, high-quality, flexible, butyl gunnable sealant for splice joints, exterior perimeters, end dams and glazing seals. It is designed for use on working and nonworking joints, most substrates and non-exposed curtainwall joints. Excellent resistance to UV. Not intended for water immersion.

Meets the requirements of Federal Specification TT-S-001657.

0110390 BLACK

DAP DYNAFLEX 230 ELASTO-MERIC LATEX SEALANT



Superior flexibility, durability, easy tooling, paintability and low odor. Excellent adhesion and watertight, weatherproof seal; mildew resistant when cured. Water clean-up, 50- year durability guarantee.

0110336 WHITE 10.1 FL OZ. 0110337 CLEAR 10.1 FL OZ

BOSS 378

SILICONE

100% silicone caulk provides

weatherproof and waterproof

lasts for years under extreme

seal. Remains flexible and

temperature changes,

moisture, weathering,

vibration, expansion and

wood, fiberglass, many

0112004 CLEAR

0112005 WHITE 0112006 BLACK 0112008 ALMOND

contraction. Bonds to metal,

plastics and concrete. 10 oz.

glass, porcelain, ceramics,

CAULK

DAP KWIK SEAL **TUB & TILE** CAULK

Bonds like a glue and seals like a caulk. Provides a durable. watertight seal, excellent adhesion and flexibility. Tools easily, paintable, water clean-up.

0119003 CLEAR 5.5 OZ 0119000 ALMOND 5.5 OZ 0119002 WHITE 5.5 OZ 0119001 WHITE 10.3 OZ



BOSS 357 LATEX

Single component, nonsag, guns easily. Flexible with excellent adhesion to common building materials. Minimal shrinkage. Tack free in 30 minutes. UV stable. Soap and water clean-up.

CAULK

20-year life expectancy. 10 fl oz

0119007- WHITE



DAP WINDOW **GLAZING/CAULK**



Smooth, easy-working compound for glazing wood, metal, and aluminum sash. Resists cracking, sagging, and chalking. Gun grade. 10.1 fl oz.

0110365 WHITE

PRO FLEX® TRIPOLYMER CAULKING SEALANT

Single component, high performance elastomeric sealant. Super flexible, excellent adhesion even when damp, UV resistance, mildew resistant, resealable, may be applied over itself, asphalt compatible, paintable, no dirt pickup; easy to apply, non-stringing formula. 10 fl. oz.

0110383 CLEAR



78

GEOCEL ALL-IN-ONE CAULK

Low VOC. Tools easily. Bonds to most common building materials. Tack free in 70 to 90 minutes. Paintable in 10 minutes. Soap and water cleanup. Water resistant in 3 hours. Mildew resistant. Meets LEED & NAHB guidelines.

0110381-10 OZ.



Geocel 🍋

Silicone & Caulks

Adhesives

STA'-PUT SPRAY ADHESIVE (SPM)

An excellent choice for most permanent or temporary adhesive applications such as bottom board and vinyl trim. Is resistant to water, is fast drying and has a long working time.



0110250 16 OZ.; 12/CTN.

STA'-PUT II SPRAY ADHESIVE (SPII)



Spray directly onto polystyrene safely with no melt-down. Ready to bond in four minutes. Water resistant. Especially formulated for Styrofoam.



0110252 13 0Z.; 12/CTN.

STA'-PUT HIGH TEMP SPRAY ADHESIVE (SPH)

For use where high temperatures are an issue. Flame resistant to approx 225 F. Non-flammable after tacked. Welds onto surface after about one minute. Not as tacky to the touch, but offers a much stronger bond once cured.



0110256 15 OZ.

STA'-PUT S203 REMOVER AND DEGREASER



STA'-PUT S203 is a biodegradable, natural solvent cleaner, degreaser and adhesive remover. It can be used safely on most surfaces and substrates, including painted surfaces, glass, porcelain, concrete, and many plastics and vinyl. S203 can be used to remove adhesives, grease, oil stains, road tar, rubber marks, and many others. S203 has a pleasant citrus scent.

0110254 14 OZ AEROSOL CLEAR

A RECEAL AGE OF A REAL AGE OF



Premium rubber-based adhesive bonds with virtually all materials, including wood, steel, plaster and concrete.

Waterproof. Sheer strength exceeding 400 psi — twice the

strength of most other adhesives in a similar class. 10.5 oz.

PROJECTS

0110255 FOR INTERIOR PROJECTS 0110257 FOR SUBFLOORS (EXTERIOR) 0110258 FOR TUBS AND SURROUNDS 0110259 FOR TUBS AND SURROUNDS VOC COMPLIANT 0110261 CONSTRUCTION GRADE WEATHER ADHESIVE POLY

LIQUID NAILS

UBFLOORS

GORILLA GLUE

The product that started it all. Gorilla Glue is known for its industrial holding power and versatility, regardless of the substrate. Easily bonds wood, stone, metal, ceramic, foam, glass and more!



0110280 2 0Z. ADHESIVE 0110281 4 0Z. ADHESIVE 0110283 GORILLA SUPER GLUE 15 GRAM BOTTLE 0110284 GORILLA SUPER GLUE 3 GRAM BOTTLE 2/PK 0110285 GORILLA TAPE 1.88IN X 35 YD 0110286 GORILLA TAPE TOUGH AND WIDE 2.88IN X 30YD 0110287 GORILLA EPOXY .85 0Z. 0110288 SINGLE USE TUBES 4/PK

HOMAX WALL & CEILING **RFPAIR PATCH**

For drywall, plaster and other flat surfaces. Metal patch with selfadhesive mesh backing permanently repairs holes in walls and ceilings. Refinish to create an invisible patch. Ideal for quick repair of interior drywall and plaster surfaces.



0260417 6" PATCH

EASY-TOUCH KNOCKDOWN TEXTURE

Water-based. Matches knockdown "Mediterranean" and splatter-type wall and ceiling textures. Two different application straws allow you to choose between medium or heavy patterns. Patches small areas up to 8 sq. ft. Single can provides up to 16 sq. ft. coverage.

0185025 20 OZ.



EASY-TOUCH ACOUSTIC TEXTURE

Patch "popcorn" or "cottage cheese" type ceiling textures fast. Contains actual polystyrene chips to match commercially applied ceiling textures.

Patch small areas up to 2 sq. ft. 16 oz.



coustic

exture

0185028 COARSE



EASY-TOUCH SPRAY **TEXTURE**

Fast-drying, oil-based. Three color-coded straws let you choose the perfect match for "orange peel" splatter textures. Up to 100 sq. ft. coverage.

0185026 20 OZ.



EASY-TOUCH DRYWALL SPRAY TEXTURE

Water-based. Fast and easy way to patch orange peel and splatter drywall textures with the advantage of low odor and water cleanup. Different size spray patterns (fine, medium, and coarse) achieved with 1 of the 3 included colorcoded straws. Covers up to 70 sg. ft. f or one 20 oz. can.



0185024 20 OZ

BATH/TUB REPAIR KIT

Comes with everything for the most demanding repairs to all types of plastics, fiberglass and even enamel bath fixtures. Shower stall cracks can be repaired in minutes. For both white and almond.



KILZ UPSHOT

Dependable Kilz stain-killer in a can, perfect for hard-to-reach places. Can even be used upright for ceilings.

0185004 10 OZ. AEROSOL



KILZ PRIMER-SEALER-STAIN KILLER

Oil Based

White pigmented primer for wood, plaster, drywall and burned areas. Seals in water stains, pen, lipstick, crayon, grease and oil stains. Recoat in 30-45 minutes. Easy clean-up with paint thinner. Mild odor. Coverage: approx. 400 sq. ft. per gallon.

0185006 13 0Z. SPRAY; 12/CTN.



Miscellaneous Supplies

DAP WALLBOARD JOINT COMPOUND

Smooth, high quality finishing of gypsum panel joints. 3 lb. tub



0119006

WALLBOARD PAINT



Off-White - 5 gallon

0185038

PUTTY KNIFF

High impact plastic. 3.5" long handles and 3.5" long blades. Hang hole.

0381105 2" 0381106 3"

SPECTRACIDE WASP AND HORNET **KILLER**

Spectracide 20 oz. Wasp and Hornet Killer eliminates wasp and hornet nests by killing insects on contact. It lets you spray nests with a 27 ft. jet spray. It won't stain the areas where it is applied when used as directed. It is formulated for outdoor control of dangerous stinging pests.



0181818 20 0Z. CAN

FIN TOOL

All metal tool straightens and cleans condenser and evaporator fins. Works on all units. Heavy-duty spring wire bristles automatically adjust to all spacings.

Tension adjustment band allows maximum rigidity and ease of operation. Straightens even the most severely damaged fins.

0380028





VENT MATE REGISTER AIR FILTERS

Fits most registers. Non-toxic. Excellent for allergy sufferers and asthmatics. Easy to install in just seconds. Fragrance lasts approximately three months. Packaged for pegboard display. Saran-coating locks in fragrance.

Traps and controls:

- Pollen
- Dust and dust mites
- Tobacco odors
- Mold, mildew and fungi spores

0180207 BABY POWDER; 3/PK.

COIL & FIN CLEANER/ DEGREASER

RCD Coil and Fin Cleaner cleans and degreases air conditioning and refrigeration equipment (Condenser & Evaporator Coils) to insure efficient operation and to help prevent overheating and motor burnout due to accumulated dust, dirt and grease in air spaces.

Contains no solvents, acids or alkalies.

Use on automobile radiators, heat pumps, electrostatic filters, refrigerators, air conditioners and cooling units. Eliminates the need for high pressure sprayers or bulky tank sprayers.

Heavy Duty Foaming, Water-Based, Powerful Blast Spray.

0181375 19 FL OZ. CAN



ZOOM OILER

All-purpose oil with extra long telescoping nozzle for hard-to-reach places. Nozzle can be retracted when not in use. 4 oz.

Use as 100% spray to quickly

and easily remove even stubborn

streaks caused by window and door

Will not harm painted finishes. Also

removes tree sap and bugs.

0180804 32 0Z.; 4/CTN.

C/AIVICO

0180101 12/CTN.

sealants.



WD-40 LUBRICANT

General purpose lubricant stops squeaks, loosens rust and protects metals. Spray can with extension nozzle for hard-toreach places. 8 oz.

0180104 12/CTN.



BLACK STREAK REMOVER By Camco. Removes

By Camco. Removes black streaks, renews sheen to metal, fiberglass, plastic, wood, painted or acrylic surfaces and other hard surfaces. Non-flammable, nonabrasive.



0180801 32 OZ.

BOSS BIGGIES DUAL SIDED ABRASIVE WIPES

Dual sided abrasive wipes clean paint, adhesives, oils and more from hands, tools and surfaces.

0181401 80 WIPES / TUB

Wipes

ALL-DIRECTION INSULATING FOAM

All-direction dispenser lets you apply foam from any direction or angle, even upsidedown or sideways.

0112010 12 OZ





RCD INDUSTRIAL HAND

RCD INDUSTRIAL HAND CLEANER

Fine pumice for quick cleaning action. Skin conditioners and an antiseptic ingredient that prevents dry, cracked hands. The waterless hand cleaner of choice for HVAC mechanics, service technicians, plumbers, electricians, auto mechanics, machinists, and printers.

Removes dirt, oil, grease, ink, paint, adhesives, asphalt, tar, and more. Does not contain d-limonene or lanolin. Packaged in sturdy plastic 16 fluid ounce squeeze bottle.

If your hands are dry and cracking or you're allergic to d-limonene or lanolin; you need #72 Industrial Hand Cleaner®.

0181410



CPDS SERIES 2 SYSTEM Constant Pressure Dispensing System



FEATURES:

- 2X faster foam delivery and up to 20% greater yield than disposable foam kits
- Foam dispenses from cylinder bottom, resulting in virtually no chemical waste
- Economical lower cost per board foot than kits
- Commonly available replacement parts
- Ideal for business start-up or service expansion
- High profit center, low maintenance
- Eliminates the need for bulk systems in midsized projects



 0112155
 CPDS SERIES 2 SYSTEM

 0112151
 TANK FOAM KIT CP-750 FR (1.75 PCF) (A & B CHEMICALS ONLY)

 0112152
 TANK FOAM KIT CP-1200 FR (1.0 PCF) (A & B CHEMICALS ONLY)

 0112160
 30' HOSE SET

 0112161
 100' HOSE SET

 0112162
 150' HOSE SET

 0112163
 SPRAY FOAM APPLICATOR WITH 12" HOSE OUTS

TWO-COMPONENT POLYURETHANE FOAM KITS

Portable, disposable and self-contained with color-coded, pre-connected hoses. These kits are available in sizes from 15-600 board feet and provide a quick consistent flow of foam that dries in under a minute. Foam expands 30X.

Fire Retardant (FR) and High Density (FK120) Formulas are available.



ITEM NO.	FOAM KIT	PRODUCT #	YIELD - BOARD FEET	YIELD - CUBIC FEET
0112119	STANDARD FORMULA FOAM KIT 15	4004520015	15	1.25
0112101	STANDARD FORMULA FOAM KIT 110	4004520110	110	9.1
0112102	STANDARD FORMULA FOAM KIT 200	4004520200	200	16.6
0112104	STANDARD FORMULA FOAM KIT 600	4004520600	600	50.0
0112109	STANDARD FORMULA FOAM KIT 600 WITH NO ACCESSORIES	4004520601	600	50.0
0112107	FIRE RETARDANT FOAM KIT 200	4004001200	200	16.6
0112108	FIRE RETARDANT FOAM KIT 600	4004521600	600	50.0
	HIGH DENSITY FOAM KIT 120 (3.0 PCF)	4004523120	120	10.0

QUICK CURE ONE COMPONENT CYLINDER FOAM



The easy portable way to handle large jobs. Available in High-Yield and Reduced Expansion formulas.

System includes hose and wands.

- Density 1.3-1.8 lbs./cu.ft.
- R Value 4.5 per inch thickness
- Max. Service Temp for Cured Foam 240°F (116°C)
- Shelf Life 12 months
- Flame Spread 20
- Smoke Developed 25
- ICC-ESR-1926

0112124 10 LBS 0112126 16 LBS 0112127 16 LB TANK ONLY 0112128 RX ORANGE 16 LB REPLACEMENT

ALL SEASON FOAM

24 oz. One component, moisture curing polyurethane foam sealant is uniquely formulated to perform under difficult low temperature conditions where traditional polyurethane foam sealants fail to cure.

Protects against both vapor migration and energy robbing air infiltration, helps to improve indoor air quality and provides superior insulation performance.

0112122



GUN FOAM II FIRE BLOCK FOAM SEALANT

Gun Foam II

Vo-Warp Fo

ICC code complying fire block penetration sealant suitable for Type V residential constructions. The bright orange color alerts building inspectors that this foam has been tested with modified ASTM-814 and UL-1715 and evaluated by ICC-ES (ESR-1926).

Withstands flaming twice as long as the leading competitor, lending crucial seconds to dangerous situations. Gun Foam II is not a firestop.

0112120

NO-WARP[®] FOAM

- Low pressure will not warp window frames or door jambs
- Exerts up to 90% less curing pressure than other foams
- Provides water-resistant, airtight seal
- One can seals up to 12 windows (36" x 60"; 3/8" gap; 1" deep)
- Bright white
- Remains flexible and easy to trim
- ICC ESR-1926 approved fireblock

0112121

FOAM APPLICATORS & ACCESSORIES

- 0112110 SPRAY FOAM APPLICATOR W/30' HOSE/ACCESSORIES (STANDARD ACCESSORY PACK CONTAINS: 8 CONICAL NOZZLES, 2 FAN NOZZLES, 1 WRENCH, 1 LUBE, 2 LATEX GLOVES)
- 0112165 SPRAY FOAM APPLICATOR W/12" HOSE OUTS (CPDS & REFILLABLES)
- 0112132 NOZZLE KIT CLEAR (2X) CONICAL (ALL TWO COMPONENT FOAMS)
- 0112131 NOZZLE KIIT YELLOW (2X) FAN (ALL TWO COPONENT FOAMS)
- 0112115 10" WAND DISPENSING KIT (10" WAND APPLICATOR & 10'GRAY HOSE) (ONE-COMPONENT CYLINDERS)

POLYURETHANE FOAM GUN CLEANER

12 Oz. PolyClean. Easily cleans wet foam from hands, tools and applicator guns. Attach directly to the gun basket to flush barrel. Insert attached adaptor into valve opening and press to dispense a small amount of Poly-Clean to a cloth for cleaning hands, tools, and gun baskets.



HANDI TOOLS



H300 DISPENSING GUN, WITH PLASTIC HANDLE

- Adjustable bead control
- Durable construction
- Solvent resistant

0112025

FOMO //.



H500 DISPENSING GUN, STEEL HANDLE AND TIP

- Adjustable bead control
- Durable construction
- Solvent resistant
- Non-stick teflonized basket

0112026

22" STEEL DISPENSING GUN

Ergonomic design for subfloor and other hard to reach applications

0112028

H700 DISPENSING GUN, STEEL REPLACEABLE PARTS

- Adjustable bead control
- Durable metal construction
- Solvent resistant
- Non-stick teflonized basket and needle valve
- Replacement parts available

0112027

10" HANDI-GUN HOST ASSEMBLY

0112069

REPLACEMENT NOZZLES

Fan nozzles dispense foam in a fan pattern and are best for spraying larger open area surfaces, such as walls and between floor and ceiling joists.

Cone nozzles are designed to dispense in a steady stream, this makes them ideal for closed wall cavities and large voids.





CONE SPRAY NOZZLE 8/PK.

FOMO //

CIFANFR Handi Cleaner cleaning

HANDI

agent, used to dissolve uncured or fresh polyurethane foam as well as dispensing guns.



0112014 12 OZ.

FOMO //

HANDI FOAM

Polyurethane Sealant with straw applicator.

0112023 12 OZ. 0112012 20 OZ. 0112011 29 OZ. 0112021 24 OZ. .









0112031 FAN SPRAY NOZZLE 8/PK.



HANDI SEAL® Window & Door Sealant

This closed cell, low pressure build window and door foam is compliant with AAMA 812-04, does not post expand or shrink more or less than 10%, and will not bow window and doors. Features a Dry Seal Technology said to prevent moisture and mold problems by repelling water.

0112013 REQUIRES DISPENSING GUN. 24 OZ. PRESSURIZED CAN 0112020 WITH STRAW APPLICATOR, 24 OZ. PRESSURIZED CAN





Foam Insulation COATINGS & CLEANERS

HANDI FOAM Polyurethane Sealant

Polyurethane foam sealants are moisture-cured, designed to completely fill and seal small gaps, cracks and voids. This one-component polyurethane is used in a bead application.

0112019 TANK ONLY 7128 BEAD FT., (I-160) 0112018 TANK W/ACCS. 8688 BEAD FT.,(I-160) 0112038 TANK ONLY 11406 BEAD FT.,(I-260) 0112039 TANK W/ACCS. 13914 BEAD FT.,(I-260)

FOMO //.



HANDI FOAM QUICK CURE SPRAY FOAM

Fomo's disposable foam kits are chemically cured, two-component polyurethane froth foam kits, designed to fill large voids and surfaces. Cures in minutes. Kits are packaged with the patented Handi-Gun[®].

0112015 COVERS 205 BD FT 0112016 COVERS 105 BD FT 0112017 COVERS 605 BD FT 0112042 COVERS 22 BD FT 0112041 COVERS 12 BD FT







HANDI FOAM FIRE BLOCK



Closed cell polyurethane sealant, provides an R-value of 4-5/inch. Orange colored for easier ID by codes officials. Pressurized can. Requires dispensing gun.

0112022 FIREBLOCK SEALANT. 24 OZ.



HANDI FOAM E-84 CLASS 1



Meets building code requirements for class 1 materials.

0112037 HANDI FOAM E-84 CLASS 1 FS25 Contains flame retardants in order to meet the testing requirements of ASTM E-84, a Flame Resistance Rating. This foam is not fire proof. Covers 105 Bd Ft.

0112045 2 PART W/RETARDANT E-84, 205 BF (P10726)



INSULATION



STOCK #	ITEM DESCRIPTION	MANUFACTURER	
0270403	APPLEGATE LOOSE FILL CELLULOSE 26.5 LBS	APPLEGATE MANUFACTURING	
0270405	APPLEGATE STABILIZED CELLULOSE 26.5LBS	APPLEGATE MANUFACTURING	
0270409	APPLEGATE BORATE CELLULOSE 26.5 LBS	APPLEGATE MANUFACTURING	
0270400	INSUL-SAFE SP FIBERGLASS BLOWING INSULATION	CERTAINTEED CORP INSULATION GROUP	
0270404	CERTAINTEED OPTIMA BLOWING INSULATION	CERTAINTEED CORP INSULATION GROUP	
0270410	15X93 BATT R-19 8/BAG CERTAINTEED	CERTAINTEED CORP INSULATION GROUP	
0270411	15X48 BATT R-38 7/BAG CERTAINTEED	CERTAINTEED CORP INSULATION GROUP	
0270412	23X48 BATT R-38 6/BAG CERTAINTEED	CERTAINTEED CORP INSULATION GROUP	
0270413	23X93 BATT R-19 8/BAG CERTAINTEED	CERTAINTEED CORP INSULATION GROUP	
0270414	15.25X94 BATT R-19 8/BAG	CERTAINTEED CORP INSULATION GROUP	
0270415	23X96 BATT R-19 UNFACED 8/BAG	CERTAINTEED CORP INSULATION GROUP	
0270416	16X96 R-19 FOIL FACED BATT 8/BAG	CERTAINTEED CORP INSULATION GROUP	
0270417	24X48 R-19 FOIL FACED 16/BAG	CERTAINTEED CORP INSULATION GROUP	
0270418	24X48 BATT R-30 KRAFT 8/BAG	CERTAINTEED CORP INSULATION GROUP	
0270419	16X48 BATTR-30 KRAFT 11/BAG	CERTAINTEED CORP INSULATION GROUP	
0270421	15X93 BATT R-13 KRAFT 13/BAG	CERTAINTEED CORP INSULATION GROUP	
0270422	23X93 BATT R-13 KRAFT 13/BAG	CERTAINTEED CORP INSULATION GROUP	
0270423	15X105 BATT R-13 KRAFT 13/BAG	CERTAINTEED CORP INSULATION GROUP	
0270388	15X48 BATT R-19 18/BAG	CERTAINTEED CORP INSULATION GROUP	
0270406	GREEN FIBER LOOSE-FILL CELLULOSE	GREEN FIBER	
0270389	48IN X50FT SINGLE FOIL FACED R-11	GUARDIAN BUILDING PRODUCTS	
0270390	6FT X 50FT SINGLE FOIL FACED R-11	GUARDIAN BUILDING PRODUCTS	
0270391	48IN X 50FT DOUBLE VINYL FACED R-11	GUARDIAN BUILDING PRODUCTS	
0270392	6IFTX 50FT DOUBLE VINYL FACED R-11	GUARDIAN BUILDING PRODUCTS	
0270393	6FT X 50FT R-11 FGLS SINGLE SIDED WPSK	GUARDIAN BUILDING PRODUCTS	
0270394	4FT X 50FT R-11 FGLS SINGLE SIDED WPSK	GUARDIAN BUILDING PRODUCTS	
0270402	ATTIC GUARD PLUS FIBERGLASS INSULATION	GUARDIAN BUILDING PRODUCTS	
0270407	15X93 BATT R-19 10/BAG GUARDIAN	GUARDIAN BUILDING PRODUCTS	
0270408	23X94 BATT R-19 10/BAG GUARDIAN	GUARDIAN BUILDING PRODUCTS	
0270397	CELLPAK ADV CELLULOSE 25LB BAG	SERVICE PARTNERS OF THE CAROLINAS	
0270398	STBLZED CELLULOSE - 28LB BAG	REGAL INDUSTRIES INC.	
0270401	CELLULOSE INSULATION - PRO 50 BY REGAL	REGAL INDUSTRIES INC.	
0270440	16" 500/BAG INSULATION HANGERS		
0270441	23" 500/BAG INSULATION HANGERS		
0270442	24" STD R-VALUE RULER		

INSULITE LIGHT COVERS

A fire retardant cover designed to allow safe and effective insulation around recessed lights. Without proper insulation, areas around recessed lights can

allow a large amount of heat energy to enter/escape from a building and become a fire hazard as well. When installed, this insulation allows closeness to the light or heat producing fixture as possible without the risk of fire.

0270444 12.5" X 14" CARDBOARD 0270452 10" X 10" X 12" METAL, VENTED



TVM BAFFLE VENTS

TVM Baffle Vents is designed for use in attics to provide an ventilation passage between your insulation and the roof.

0270439 WINDBLOCK ™ CARDBOARD 24" X 23" 0270446 DUROVENT 23.5" X 46", 70 PER BAG 0270449 TVM 22" X 48", 50 PER BAG



PINE WOOD PLUGS

Slightly tapered for easy insertion. The top 1/8 is the full diameter measurement for a tight even fit. Made from kiln dried lumber and produced on specially designed equipment, resulting in quality, uniformly-sized plugs. No splintered face edges. Packaged in 250 count bags

0270428 2" PLUG, 250/BAG 0270434 2 1/2" PLUG, 175/BAG 0270435 2 9/16" PLUG, 175/BAG





The Long Nose, with its exceptional design, is our best plastic plug. With a 5/8" shank and heavy gripping teeth, this plug will hold in both single and multiple layers of siding. Extra wide cap has a tapered edge for obscured vision on sidings and a textured top for easy painting. 250 per bag. 2000 per box.

0270424 2 1/2" PLUG, 250/BAG 0270426 2" PLUG-LONG BARREL



FOAM DRYWALL PLUGS

Styrofoam plugs used for holes in drywallrecessed to accept spackling compound. They absorb little moisture, thus require fewer layers of spackling for a smooth finish. 1000 per package.

0270432 2 1/2" PLUG, 750/BAG 0270433 2 9/16" PLUG, 750/BAG



FORCE/2 INSULATION BLOWER

Professional Grade – Virtually Indestructible!

The FORCE/2 is the insulation blower you want when you need a larger, stronger machine. With an 8½ cu. ft. hopper that can hold 50 lbs of material, a strong 1½ hp motor and a powerful 3.6 PSI blower, the FORCE/2 blows up to 2,012 lbs of fiberglass per hour. And for the more demanding jobs, the FORCE/2 is now available with an incredible 4.5 PSI, 116 CFM blower. Easy setup, operation and cleanup. It takes only four switches to operate the FORCE/2. No complicated gauges, dials, or knobs.

0380453

WASP INSULATION BLOWER

The WASP represents the best insulation blowing technology available, refined and enhanced with your ideas and suggestions. What's more, the WASP utilizes proven airlock technology for simplicity and minimal downtime. The result is the best lightweight machine on the market, tailored to meet your demanding requirements.

0380412 - 816E FIBER HANDLING SYSTEM

FORCE/3 INSULATION BLOWER

High production at 2520 lbs of cellulose & 1350 lbs of fiberglass per hour. Portable. Dual blowers. 3.0 or 4.0 PSI. Long life seals

0380454





BLOWER ACCESSORIES:

HOSE:

0380422 2" MARK II CLEAR HOSE X 50' 0380423 2-1/2" MARK II BLUE HOSE X 50' 0380424 3" MARK II CLEAR HOSE X 50' SWIVELS: 0380425 2" HOSE SWIVEL 0380426 2-1/2" HOSE SWIVEL 0380427 3" HOSE SWIVEL MISC. ACCESSORIES: 0380415 2" TO 1" WALL NOZZLE 0380416 1-1/4" X 10' WALL TUBING 0380417 3" TO 2-1/2" REDUCER 0380418 2-1/2" TO 2" REDUCER 0380419 3" SS HOSE CLAMP 0380420 2-1/2" SS HOSE CLAMP 0380421 2" SS HOSE CLAMP Insulation Accessories



TVM REFLECTIVE SINGLE OR DOUBLE BUBBLE POLY INSULATION

TVM Poly-Reflective Insulation is a single or double layer of polyethylene bubbles, sandwiched between a highly reflective surface, and a white polyethylene sheet. It is ideal for many residential and commercial building applications, including walls and ceilings.

Products in this line are classified as Class 1 / Class A in accordance with the ASTM-E84 fire test standard. These products also pass the NFPA 286 Full Room Burn Test, and contain UV inhibitors help provide a durable and lasting finish. 94% Reflectivity for optimal thermal performance. Building application – R-10 when installed with 3/4" sag between joists.

POLY/SINGLE BUBBLE/REFLECTIVE

0270547 48" X 125' (500 SQ/FT) SQUARE EDGE 0270549 72" X 125' (750 SQ/FT) SQUARE EDGE 0270550 84" X 125' (875 SQ/FT) SQUARE EDGE

POLY/DOUBLE BUBBLE/REFLECTIVE

0270566 48" X 125' (500 SQ/FT) SQUARE EDGE 0270536 72" X 125' (750 SQ/FT) SQUARE EDGE 0270537 84" X 125' (815 SQ/FT) SQUARE EDGE 0270538 72" X 102' (612 SQ/FT) QUICK SEAM



REFLECTIVE SINGLE OR DOUBLE BUBBLE INSULATION

TVM Reflective Insulation is a single or double layer of polyethylene bubbles, sandwiched between two highly reflective metalized surfaces. Typical system R-values incorporating TVM's Reflective Insulation, range from R-6.6 to R-15.2, and all products in this line are Class 1/Class A in accordance with the ASTM E84 fire test standard.

In addition to increasing the thermal resistance of a building envelope, all of TVM's bubble-core products are approved vapor barriers. 94% Reflectivity for optimal thermal performance. Building application – R-10 when installed with 3/4" sag between joists.

SINGLE BUBBLE REFLECTIVE

0270551 60" X 125' (625 SQ/FT) SQUARE EDGE 0270548 7 2" X 125' (750 SQ/FT) SQUARE EDGE

DOUBLE BUBBLE REFLECTIVE

0270545 48" X 125' (500 SQ/FT) SQUARE EDGE 0270546 72" X 125' (750 SQ/FT) SQUARE EDGE



TVM Reflective Duct Insulation is a double layer of polyethylene bubbles, sandwiched between two layers of highly reflective metalized sheets. This product has a code certification strip that identifies the brand name and pertinent testing information for duct applications. This inspector friendly tape means no hassles at the jobsite, and peace of mind for installers.

TVM has developed and tested three possible installation schemes - R-4.3 if directly applied to duct, R-5.5 if use of reflective spacers, R-6 if used with foam spacers. All products within this line are classified as Class 1/Class A in accordance with the ASTM E84 fire test standard. Approvals: T24 CA-T354 (CN). Approved vapor barrier protection. Inhibits condensation, mold and fungi growth. Thermal performance unaffected by moisture. Nontoxic & Non-carcinogenic.

DOUBLE BUBBLE FOIL - 1 ROLL PER BUNDLE

0270531 36" X 50' - 200 SQ.FT. 0270534 48" X 50' - 200 SQ.FT. 0270529 48" X 100' - 400 SQ.FT. 0270532 48" X 125' - 500 SQ.FT. 0270535 60" X 100' - 500 SQ.FT.



TVM TAPES

Made of a special UV metalized polypropylene film, with a high tack acrylic adhesive. These tapes can help maintain a complete seal in radiant barrier system and are resistant to moisture, flame spread, and smoke generation.

High temperature resistance makes TVM Tapes ideal for use in heat repelling applications.

0270530 2.5"X 180' UL 181 APPROVED TAPE (DUCT APPLICATION) 0360430 2"X 150' WHITE POLY TAPE 0360710 3"X 150' WHITE POLY TAPE